

# Specification Data Positioners Capacity: 250kg Fixed Height

## LPE0.25-WD

**Harbach Positioning** Positioner Model LPE0.25-WD Series is designed to give maximum positioning flexibility by using the tilt and rotation of the table to manipulate the work piece into the correct 'down hand' position for welding or to position accurately for assembly and manufacturing requirements. The table is machined with four radial slots for anchor bolts and centric marking on the surface table, a set of tapered bearing mounted below the table to give a smooth and constant turning during operation. Driven by a DC motor with variable speed, controlled by a standard control pendant with low voltage push button and potentiometer with a 3-meter control cable built in. Tilt movement is electrically powered driven by 500W DC motor with dynamic braking through reducer gearbox. Built in with 300amps rotary clamp to ensure good earthing to the welding power source.

Table diameter 500mm.




### **Specifications**

Model: LPE0.25-WD Pendant Control: 24VDC circuit, push button with 3-meter cable Input voltage: 220V/1phase/50Hz (specify voltage requirement when ordering) Rotation Capacity: 250kg at 300mm Rotation Speed: 0 to 4 rpm Tilting Capacity: 250kg at 300mm c of g Tilt Range: 0 to 135 Degrees Tilt Speed: 135 degrees in 30 seconds Rotation Drive Motor: 100W motor Rotation Drive Control: DC motor card Tilt Drive Motor: 500W DC Estimate weight: 230kg

## LPE0.25-WD (250kg)


218 W. Richey Road Houston, TX 77090 Positioning.Har-Bach.com sales@har-bach.com


1	Model	LPE0.25-WD			
2	Capacity (Turning)	250kg@300mm(Please refer to load chart)			
3	Capacity (Tilting)	250kg@300mm(Please refer to load chart)			
4	Electrical Panel	Yes			
5	Rotation Speed/power	0-4rpm AT 0-90V /DC 100W			
6	Tilt Range/power	0-135' in 30sec/DC 500W			
7	Incoming Supply	220V-1P-50HZ			
8	Control Voltage	24VDC			
9	Rotation Drive Control	DC Motor Card			
10	Control Means	Foot Switch (Toggle Type) c/w 3m Cable			
11	Talole Size	Ø500X20t C/W 4X slot(18)			
12	Earthing	300A			
13	Surface Preparation	Gritblast to SA2.5			
14	Painting	Powder Coating			
15	Color	RAL 3003 RED & RAL9005 BLACK FOR TILTING BOX AND TABLE			
16	Qty	1 unit			
17	Est Weight(kg)	220			
18	Shipping dimension/cm	93(L)X70(B)X77(H)			



#### Note::

1] This drawing is accurate at time of preparation and may be subjected to final design.





All dimensions in mn unless otherwise specified. REV DATE DESCRIPTION EDIT BY REMARKS					
	CUSTOMER APPROVAL	CHECKED BY:	DRAWN BY:	CUSTOMER	SCALE: N.T.S.
	drawing name 250kg Positioner				
				drawing nd: LPE0.25-WD	revision 2
			29-11-2010	THE ORGINAL AND ALL COPIES OF THIS DOCUMENT TOGETHER WITH THE COPYRIGHT THEREOF ARE THE SOLE PROPERTY OF HARBACH MARKETING, INC. DESIGN AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PROXIMITIES	SHEET: 1.0F.1